

EC-IP4655U

4MP 100M IP Underwater PTZ POE Camera



Key features:

- 1/3 inch 4Megapixel progressive scan CMOS Sensor;
- 2560*1440@60fps;
- IP68, POE Max. water depth: 100m;
- Focus f=2.7-14mm(F1.8-3.2) 5X Optical zoom;
- Multiple network monitoring: Web viewer, CMS;
- Max.32 preset.support preset recover if power off or ;
- dislocationHousing material: stainless steel 316L;
- Attachment bar: adjustable by 180;
- Toughened safety glass (ESG) ;
- TVS lightning protection to avoid 1.5KW thunderstrike.

Model		EC-IP4655U
Camera Type		4MP IP Underwater PTZ POE Camera
Camera	Image Sensor	1/3" 4MP CMOS
	Effective Pixels	4MP 2560*1440
	Min.Illumination	Color 0.5Lux/F1.4
	Electronic Shutter	1/50(1/60)s-1/100,000s
	Lens	2.7-14mm(F1.8-3.2) 5XOptical zoom
	Lens Mount	M12/CS Mount
	Material	stainless steel 316L
Compression	Compression Standard	H.265++/H.265+/H.265/H.264
	Video Frames	PAL/NTSC 4MP@1~60FPS
	Video stream output	Support adjustable stream 0.1M ~ 10Mbps
Image	Quality	3D-DNR,BLC,AWB,auto ISO
	Resolution	Main Stream: 4MP 2560*1440@60fps; 3MP 2048*1536@25fps;2MP 1920x1080@30fps;1280x720(1MP) 30fps
		Sub Stream: 640x360,720x480(1-30fps)
Network	Parameter Settings	WEB configure and OSD supported, Real time recording, Transmission and playback
	Basic	Dual stream, Password protection
	Protocol	RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP
	Alarm	Support Motion Detection, Linkage Alarm, Linkage recording, Sensor trigger alarm functions
Interface	Video Output	RJ45
	Network Interface	1 RJ45 Ethernet interface, 10/100M adaptation
PTZ	Pan / tilt	Pan 355 degree , Tilt 0-90degree
	Manual Speed	0.5360/s ~360 /s continuously adjustable
Other	Work Environment	-10°C- +60°C
	Waterproof Criterion	IP68
	Power Supply	POE IEEE802.3at/af
	Size	Ø 160 x 150 mm
	Cable	CAT6
	Net Weight	N.W.5kg +cable 0.12kg/m