

DK8354-W Plastic Doorbell



▪ Key Feature

- Support talk to each other visually after calling the master station;
- Support accept the unlocking command of the indoor unit for remote unlocking;
- Support adaptive infrared light compensation;
- Adopts advanced hardware noise suppression and echo cancellation technology to ensure clear voice quality and adjustable intercom volume ;
- Equipped with a standard waterproof cover, which can be installed by the user;
- Uses a 300w camera to provide monitoring function × 24-hour preview and video recording ;
- Equipped with alarm function, which supports anti disassembly alarm;

▪ Specification

Model	DK8354-W Plastic Doorbell
System	LINUX,Single core 32-bit DSP, hard compression, watchdog, 8MB FLASH, built-in 64MV DDR
Camera	3MP 1/2.7" CMOS,colour 2.0Lux@F2.0,B/W 0 Lux@F2.0;Integrated IR cut driver,support Sensor+IR-CUT +LED Linkage control of light supplement, Day/Night
Video Compression	H.265+/H.265/H.264 code format,Double stream ,PAL/NTSC
Frame Rate	3MP@15fps
Image Output	Main stream:2304×1296, 1280×720
	Sub stream:640×360
Audio Interface	1*MIC input,1*loudspeaker output;
Audio Compression	G.711,Support two-way voice intercom function and audio and video synchronization;
Network	10/100M Base-TX Ethernet, RJ45 Connector HTTP,TCP/IP,IPv4,DHCP,NTP
Protocols	HTTP,TCP/IP,IPv4,DHCP,NTP
Signal Interface	1*IRCUT interface, support the control of IR-CUT and image linkage;
Upgrade Maintenance	Support OTA upgrade
Business Functions	Support OSD, real-time video transmission, mobile detection and human shape detection
ONVIF	UnSupport
Remote Unlock	Support
Power Supply	DC12V
Dimensions	67.32mm×66.92mm×134.34mm (W×D×H)
Working Temperature	-10°C ~+70°C

▪ Dimensions

